

[Web](#) [Images](#) [Videos](#) [Maps](#) [News](#) [Shopping](#) [Gmail](#) [more](#) ▼

[Sign in](#)

Google scholar

802.16e rssi

Search

[Advanced Scholar Search](#)

[Scholar Preferences](#)

Scholar [All articles](#) [Recent articles](#)

Results **11 - 20** of about **312**. (0.08 sec)

[... BiCMOS MIMO/Diversity Direct Conversion Transceiver IC for WiBro/WiMAX \(802.16 e\)](#)

M Locher, J Kuenen, A Daanen, H Visser, BH ... - IEEE Journal of Solid-State Circuits, 2008 - [ieeexplore.ieee.org](#)

... LOCHER et al.: BiCMOS MIMO/DIVERSITY DIRECT CONVERSION TRANSCEIVER IC FOR WiBro/WiMAX (**802.16e**) ... done with a pulsed 10 MHz QPSK Rx signal at a fixed **RSSI** of ...

[Cited by 1](#) - [Related articles](#)

[\[PDF\] •Towards a GNU/Linux IEEE 802.21 Implementation](#)

E Piri, K Pentikousis - Currently under review - [csee.usf.edu](#)

... to WE with some cards but our test measurements showed that **RSSI** provides more ... Mobile WiMAX (based on IEEE **802.16e**-2005) has recently emerged as a potent ...

[Cited by 1](#) - [View as HTML](#)

[Outdoor Path Loss Models for IEEE 802.16 in Suburban and Campus-Like Environments](#)

D De Luca, F Fiano, F Mazzenga, C Monti, S ... - ... Conference on Communications, 2007. ICC'07, 2007 - [ieeexplore.ieee.org](#)

... 2 0.6525 103.28 OS 3.533 0.6525 9.711 TABLE II P ATH LOSS EXPONENT , **RSSI** S TANDARD ...

<http://www.ieee802.org/16> [3] Standard IEEE **802.16e**-2005 available on site ...

[Cited by 1](#) - [Related articles](#)

[The Effect of a Rapidly Changing Urban Environment on Nomadic WiMAX Performance](#)

KG Filis, ED Theodoropoulou, GL ... - Mobile and Wireless Communications Summit, 2007. ..., 2007 - [ieeexplore.ieee.org](#)

... in the future, the mobility support capabilities of IEEE **802.16e**, in conjunction ... sessions, respectively, along with the Received Signal Strength (**RSSI**) and the ...

[Cited by 1](#) - [Related articles](#)

[\[PDF\] •Proposal for MS handover procedure in an MR network](#)

RG Cheng, FC Ren, CM Chou, KY Hsieh - IEEE C802. 16j-07/047r1, IEEE - [ieee802.org](#)

... After triggering inter-VC HO, the legacy **802.16e** handover procedure specified in section ... **RSSI** info 16 bits The value shall be interpreted as an unsigned byte ...

[Cited by 1](#) - [Related articles](#) - [View as HTML](#) - [All 3 versions](#)

[... Opportunity for Optimization of Various RF Parameters in IEEE **802.16 e** Multi-Cell Networks- •illinois.edu](#)

[\[PDF\]](#)

M Dillon, A Diwan, C Murphy, V Raman, M Inc ... - 2006 IEEE 64th Vehicular Technology Conference, ..., 2006 - [ieeexplore.ieee.org](#)

... approach is thus based on the assumption that the differences between 1xEV-DO and **802.16e** do not ... The MSS received signal strength indicator (**RSSI**) is used ...

[Related articles](#) - [All 2 versions](#)

HH Huang, JS Wu, SF Yang - Wireless and Optical Communications Networks, 2008. ..., 2008 - ieeexplore.ieee.org
... using Signal to Noise Ratio (SNR) or Received Signal Strength Indication (**RSSI**). ...
a clear framework of FMIPv6 handover procedure above IEEE **802.16e** which uses ...

A multiple cross-layers explicit fast handover control using MIH in 802.16 e networks

HH Huang, JS Wu, SF Yang - Wireless and Optical Communications Networks, 2008. ..., 2008 - ieeexplore.ieee.org
... of previous research in cross-layer architecture uses SNR or **RSSI** as triggers ... In
this research, we propose a handover procedure combining **802.16e**, FMIPv6, SIP ...

Related articles

[PDF] • A Proactive Horizontal Handover Algorithm Based on RSSI Supported by a New Gradient ...

K Atalah, E Macías, A Suárez - ubicc.org

... A Proactive Horizontal Handover Algorithm Based on **RSSI** Supported by a New Gradient Predictor ... The **RSSI** is used to define different areas of coverage. ...

[Related articles](#) - [View as HTML](#)

A New Handover Mechanism for IEEE 802.16 e Wireless Networks- 202.194.20.8 [PDF]

H Fattah, H Alnuweiri - ... and Mobile Computing Conference, 2008. IWCMC'08. ..., 2008 - ieeexplore.ieee.org
... The algorithm fits into the current IEEE standard for **802.16e** networks without ... Although
the **RSSI** measurement is considered as the main factor in selecting the ...

[Related articles](#) - [All 2 versions](#)



Result Page: [Previous](#) [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [11](#) [Next](#)

802.16e rssi

[Go to Google Home](#) - [About Google](#) - [About Google Scholar](#)

©2009 Google